

2	<b>CONTOUR PLOTTING</b>	5.02	...Having return coincide with swept display or detector
3	<b>RANGE OR REMOTE DISTANCE FINDING</b>	5.03	...Having one or more return pulse gates or windows
3.01	..Triangulation ranging to a point with one projected beam	5.04	....Including a displayed image
3.02	..Using photodetection with a fixed axial line of sight	5.05	...Having pulse transmission trigger significance
3.03	..Using a source beam with a fixed axial direction or plane	5.06	....Including optical pick-off of transmission start
3.04	...With a single staring photodetector having one element	5.07	....With specific counter type timing of returns
3.05	....Having moving receiver optics	5.08	....Including specific counter type timing of returns
3.06	...With a single photodetector having multiple elements	5.09	..Of frequency difference
3.07	....Having electronic scanning of the photodetector	5.1	..Of CW phase delay
3.08	...With at least one paired set of staring photodetectors	5.11	...Having multiple carrier or modulation frequencies
3.09	..Requiring scanning of a source beam	5.12	....Including an alternating reference path
3.1	..Triangulation ranging to a point with two or more projected beams	5.13	...Having an alternating reference path
3.11	..Using photodetection at the source station(s)	5.14	...Having polarization discrimination
3.12	..Using photodetection remote from the source station(s)	5.15	...Having specific IF mixing of returns
3.13	..Triangulation ranging with photodetection, but with no projected beam	6	..Instrument condition testing or indicating
3.14	..Using at least a pair of viewing axes	7	..Periscope or offset type
3.15	...With one viewing axis fixed	8	..With view finder
3.16	...With moving optical elements in all viewing axes	9	..Base line instrument (i.e., base is a part of instrument)
4.01	..With photodetection	10	..With filter or light valve
4.02	..Of a simulation or test	11	..Range finder combined with height finder
4.03	..Of focused image size or dimensions	12	..Stereoscopic
4.04	..Of degree of defocus	13	...Ortho-pseudo type
4.05	..Of focal point search	14	...Stationary measuring marks
4.06	..Of differential amplitude at two source or detector distances	15	..Length of base line variable
4.07	..Of intensity proportional to distance	16	..Image displaced by moving refracting element
4.08	..Of height relative to a light plane	17	..Image displaced by rotating reflecting element
4.09	..Of light interference fringes	18	..With mounting, supporting, adjusting, or folding structure
4.1	...Having different frequency sources	19	..Prism structure for determining coincidence
5.01	..Of pulse transit time	20	..External basis type
		21	..Object size or distance known
		22	...With displaced images
		23	<b>MOTION STOPPING (E.G., STROBOSCOPES)</b>

24	.Periodically moving reflecting or refracting element	64	.With light box
25	.Periodically moving light interrupting element	65	..With egg turning or jarring
26	..Vibrating or oscillating element	66	..With particular illumination means
27	<b>VELOCITY OR VELOCITY/HEIGHT MEASURING</b>	67	...With particular electrical switching
28	.With light detector (e.g., photocell)	68	.Lamp attachments
28.5	..Of light interference (e.g., interferometer)	69	<b>CUTTING BLADE SHARPNESS</b>
29	<b>OPTICAL ELEMENT OR RETICLE RESPONDS TO RELATIVE VELOCITY OF REMOTE OBJECT</b>	70	<b>OIL TESTING (E.G., CONTAMINATION)</b>
30	<b>CRYSTAL OR GEM EXAMINATION</b>	71	<b>DOCUMENT PATTERN ANALYSIS OR VERIFICATION</b>
31	.Axes determination	72	<b>WITH PLURAL DIVERSE TEST OR ART PLURAL TEST</b>
32	<b>MATERIAL STRAIN ANALYSIS</b>	73	<b>FOR OPTICAL FIBER OR WAVEGUIDE INSPECTION</b>
33	.With polarized light	73.1	<b>BY DISPERSED LIGHT SPECTROSCOPY</b>
34	..Attached detector	300	.With Raman type light scattering
35	..Sheet material	301	.For spectrographic (i.e., photographic) investigation
35.5	.By light interference detector (e.g., interferometer)	302	..With spectral analysis
36	<b>WITH SAMPLE PREPARATION</b>	303	..With sector disc
37	.Condensation nuclei detector	304	..With diffraction grating
38	.Depositing particles on optical surface	305	.With internal standard comparison
39	<b>BLOOD ANALYSIS</b>	306	.With background radiation comparison
40	.Hemoglobin concentration	307	.With synchronized spectrum repetitive scanning (e.g., cathode-ray readout)
41	..Oximeters	308	..Using plural beams
42	..Standards	309	.With aperture mask
43	<b>OPTICAL PYROMETERS</b>	310	.With sample excitation (e.g., burning)
44	.With sample engaging rod or tube	311	..By electrical resistance heating (e.g., graphite tube)
45	.Plural color responsive	312	..By arc or spark
46	.With incandescent standard	313	...Including sputtering
47	..Automatic intensity control	314	..By flame
48	..Modulating (e.g., flicker beam)	315	..By high frequency field (e.g., plasma discharge)
49	..Telescopic	316	..By light
50	...Current control	317	...Monochromatic (e.g., laser)
51	<b>INFRARED AND ULTRAVIOLET</b>	318	.Utilizing a spectrophotometer (i.e., plural beam)
52	<b>EGG CANDLING</b>	319	..Having plural wavelengths
53	.Photoelectric	320	..Having servo equalization
54	.With counting, marking, or weighing	321	...With polarized light beams
55	.With egg transfer	322	..Having beam modulation
56	..With egg turning or jarring	323	...With plural dispersion
57	...Endless conveyor	324	...Prior to testing
58	..Endless conveyor	325	.Utilizing a spectrometer
59	..Manual transfer	326	..Having light polarizing means
60	...With light shading chamber	327	
61	...Portable receptacles		
62	.With light shading chamber		
63	..Hood type		

328	..Having diffraction grating means	470	..Passive cavity (laser source outside cavity)
329	...Including servo slit adjustment means	471	..Multi-axis cavity
330	..Having optical gating means	472	..Lock-in prevention
331	..With monochromator structure	473	...Path length control (PLC)
332	..Having adjustable color or bandwidth	474	...Having dither signal removal from output
333	...In a double monochromator	475	...Having dither signal control
334	...With diffraction grating means	476	...By dithering (suspensions, drives, flexures)
335	<b>FOR SIZE OF PARTICLES</b>	477	.Using fiber or waveguide interferometer
336	..By particle light scattering	478	..Multiplexed sensor array
337	<b>BY PARTICLE LIGHT SCATTERING</b>	479	..Having a short coherence length source
338	..With photocell detection	480	..Resonant cavity
339	..At right angles to the light beam (e.g., nephelometer)	481	..Refraction indexing
340	..At variable angle to the light beam	482	..For distance or displacement measurement
341	..For light comparison means	483	..Plural counter-propagating beams (e.g., non-motion Sagnac device)
342	..Of back-scattered light	484	.Having light beams of different frequencies (e.g., heterodyning)
343	..Using plural photocells	485	..For dimensional measurement (e.g., thickness gap, alignment, profile)
344	<b>BY ELECTROPHORESIS</b>	486	...Displacement or distance
450	<b>BY LIGHT INTERFERENCE (E.G., INTERFEROMETER)</b>	487	....Polarization
451	..Spectroscopy	488	.....Having wavefront division (e.g., by diffraction)
452	..Having particular linear mirror drive or configuration	489	...Contour or profile
453	..Polarization	490	...Alignment
454	..Fabry-Perot type or Etalon Type	491	.Having polarization
455	..Having a rotating, pendulous, or wedge scanning element	492	..For dimensional measurement
456	..Imaging	493	...Displacement or distance
457	..Holography	494	....Having wavefront division (e.g., by diffraction)
458	..For optical configuration	495	...Contour or profile
459	..Rotation rate (e.g., ring laser gyros)	496	.For dimensional measurement
460	..By fiber or waveguide interferometer (e.g., Sagnac effect)	497	..Having short coherence length source
461	...Resonant loop	498	..Displacement or distance
462	...Multi-axis (X-Y-Z) having multiplexing	499	...Having wavefront division (e.g., by diffraction)
463	...Multiple harmonic output	500	...X-Y and/or Z table
464	...Having null feedback loop	501	...Of probe head (e.g., atomic force microscope)
465	...Fiber coil winding	502	...Surface displacement due to acoustic wave propagation)
466	...Having m x n loop coupler where (m is greater than 2) and (n is greater than or equal to 2) (e.g., passive bias)	503	..Thickness
467	..Four frequency, multi-oscillator, non-planar cavity	504	...Refraction from surfaces of different refractive index
468	..Cavity output beam combiner	505	..Gap
469	..Cavity mirror details		

506	...Fabry-Perot type	137	..Plural prisms
507	...Between slider/disc (e.g., flying height)	138	<b>ANGLE MEASURING OR ANGULAR AXIAL ALIGNMENT</b>
508	..For orientation or alignment	139	.Plural scales or different portions of same scale simultaneously observable
509	...Between mask and wafer	139.01	.Star/Sun/Satellite position indication with photodetection
510	...Tilt	139.02	..With reticle or slot
511	..Contour or profile	139.03	.Relative attitude indication along 3 axes with photodetection
512	...By wavefront detection	139.04	.Automatic following or aligning while indicating measurement
513	....Of highly reflective surface (e.g., mirror)	139.05	..With optical elements moving relative to fixed housing to follow or align
514	.....Planar surface	139.06	..With optical housing moving to follow or align
515	....Of transmission (e.g., lens)	139.07	..With photodetection of reflected beam angle with respect to a unidirectional source beam
516	...Step height (differential, between points)	139.08	...With source beam moving to follow or align
517	.For refractive indexing	139.09	.Wheel alignment with photodetection
518	..Having Schlieren effect	139.1	.Photodetection of inclination from level or vertical
519	.Having partially reflecting plates in series (e.g., Fabry-Perot type)	140	.Apex of angle at observing or detecting station
520	.Having shearing	141.1	..With photodetection of reflected beam angle with respect to a unidirectional source beam
521	.Having wavefront division (by diffraction)	141.2	..With photodetection
364	<b>BY POLARIZED LIGHT EXAMINATION</b>	141.3	...With unidirectional or planar source beam directed at the photodetecting station
365	.With birefringent element	141.4	...With optical scanning of light beam or detector
366	.With polariscopes	141.5	...With at least 2-dimensional sensitivity
367	..Including polarimeters	142	..Scale and remote point simultaneously observable
368	...With electro-optical light rotation	143	...Artificial reference
369	.Of surface reflection	144	..With plural images
370	.With light attenuation	145	...Lines of sight relatively adjustable with two degrees of freedom
121	<b>LAMP BEAM DIRECTION OR PATTERN</b>	146	...Two or more lines of sight deflected
122	.With lamp focusing	147	..Measurement in two planes (e.g., azimuth and elevation; hour angle and declination)
123	<b>FOCAL POSITION OF LIGHT SOURCE</b>		
124	<b>LENS OR REFLECTIVE IMAGE FORMER TESTING</b>		
124.5	.For optical transfer function		
125	.Focal length measuring		
126	..Deflecting or interrupting optical path		
127	.Optical center, cylinder axis, or prism measuring or determining		
128	<b>REFRACTION TESTING (E.G., REFRACTOMETERS)</b>		
129	.Schlieren effect		
130	.Differential		
131	..With servo controlled optical member		
132	...Reflective optical member		
133	.Refractive rod engages specimen		
134	.Prism forming fluid specimen container		
135	.Prism engaging specimen		
136	..Internally reflecting prism		

148	..Artificial reference	627	.Volume
149	...Gyroscope or pendulum stabilized optical element	628	.Area
150	.Sides of angle or axes being aligned transverse to optical axis (e.g., drift meter)	629	..Light scanning
151	..With light pulsing or interrupting means	630	.Thickness
152.1	..With photodetection remote from measured angle	631	..By triangulation
152.2	..With reflection of a unidirectional source beam from a planar or nonretroreflective surface	632	..Of light permeable material
152.3	..With reflection of a unidirectional source beam from a retroreflector	634	.Length
153	.Alignment of axes nominally coaxial	635	.Width or diameter
154	.With screen	636	..Line width
155	..Wheel alignment	637	..Web
600	<b>SURFACE ROUGHNESS</b>	638	..Shadow or beam blocking
601	<b>SHAPE OR SURFACE CONFIGURATION</b>	639	...Scanning
602	.Triangulation	640	....Single beam scans entire width or diameter
603	..Projection of structured light pattern	388	<b>BY CONFIGURATION COMPARISON</b>
604	...Pattern is series of non- intersecting lines	389	.With photosensitive film or plate
605	....Moire	390	.With two images of single article compared
606	..Line of light projected	391	.With projection on viewing screen
607	...Scan	392	..For comparison with master or desired configuration
608	..Scan	393	...Having master or desired configuration projection
609	.By focus detection	394	.With comparison to master, desired shape, or reference voltage
610	.By projection of coded pattern	395	.With relatively movable optical grids
611	.By stereo	396	.With scale or optical grid displaced relative to remote fiducial mark
612	.By specular reflection	397	.With object being compared and scale superimposed
613	.Silhouette	398	.With object being compared and light beam moved relative to each other (e.g., scanning)
614	<b>POSITION OR DISPLACEMENT</b>	399	<b>BY ALIGNMENT IN LATERAL DIRECTION</b>
615	.Position transverse to viewing axis	400	.With light detector (e.g., photocell)
616	..Having scale or grid	401	.With registration indicia (e.g., scale)
617	...Coded scale	402	<b>BY SHADE OR COLOR</b>
618	...Moire	403	.With merging colors or patterns (e.g., Maxwell disc)
619	....Quadrature detection	404	.Photography
620	..Special mark or target on object	405	.Tristimulus examination
621	..Occulting a projected light beam	406	.Trichromatic examination
622	..Position of detected arrangement relative to projected beam	407	.With sample responsive to plural colors applied simultaneously
623	.Triangulation	408	.With sequential comparison of sample and standard
624	.Focus	409	.Fluid color transmission examination
625	<b>DIMENSION</b>		
626	.Cavities		

410	..Of flowing liquids	214	.Pupillary
411	...With plural light detectors (e.g., photocells)	215	.Integrating
412	..With ionic determination	216	.Heat absorbing (e.g., radiometers)
413	..With variable light path length	217	.Modulating (e.g., flicker beam)
414	..With color transmitting filter	218	.Photoelectric
415	...Including liquid filter comparison	219	..Simultaneous sighting and reading measurement
416	..With color transmitting filter	220	..Multiple housings
417	..Included with sample excitation	221	..Responsive to incident or back lighting
418	..Including rotating sequential filters	222	..Plural detectors
419	..Including multicolor filters	223	..Logarithmic
420	..Included with colored light sources	224	..Multisensitivity range
421	..With reflective multicolor chart or standard	225	..With predetector light modifier (e.g., diaphragm)
422	..Plate	226	..Detector and indicator electrical coupling (e.g., amplifying or attenuating)
423	...Disk		
424	..Drum or endless tape	227	..With particular indicator
425	..With color determination by light intensity comparison	228	...Movable scale (e.g., calibrating)
426	<b>BY INSPECTION WITH AGITATION OR ROTATION</b>	229	.Comparison
427	..Of container contents	230	..With light standard
428	..Of containers	231	...Variable incandescent standard
429	<b>BY MONITORING OF WEBS OR THREAD</b>	232	...Standard movable
430	..For flaws or imperfections	233	.With variable light aperture size
431	..Including transverse scanning	234	.Light absorbing
432	<b>FOR LIGHT TRANSMISSION OR ABSORPTION</b>	235	..Absorber continuously variable (e.g., wedge)
433	..By comparison	236	.Integrating spheres
434	..Photoelectric (e.g., sequential viewing)	237.1	<b>INSPECTION OF FLAWS OR IMPURITIES</b>
435	...With plural detectors (e.g., simultaneous viewing)	238.1	.Textile inspection
436	..Of fluent material	238.2	..Elongated textile product (e.g., thread, yarn, etc.)
437	..Gas	238.3	..Detection of foreign material (e.g., trash, splinters, contaminants, etc.)
438	...Exhaust, dust or smoke		
439	....Contained	239.1	.Transparent or translucent material
440	..With significant sample holder or supply	239.2	..Optical element (e.g., contact lens, prism, filter, lens, etc.)
441	..Having particles suspended in liquid		
442	...With light detector	239.3	..Patterned surface
443	..Of photographic film	239.4	..Containers (e.g., bottles)
444	..With scanning, sweeping, or moving detector over film	239.5	...Detection of foreign matter on or in container
445	<b>OF LIGHT REFLECTION (E.G., GLASS)</b>	239.6	...Of container contents
446	..With diffusion	239.7	..Surface condition
447	..With modulation (e.g., flicker beam)	239.8	...Detection of an object or particle on surface
448	..By comparison	240.1	.Containers or enclosures (e.g., packages, cans, etc.)
213	<b>PHOTOMETERS</b>		

241.1 .Bore inspection (e.g.,  
borescopes, intrascope, etc.)

241.2 .Firearm bore inspection

241.3 .With adjustable head

241.4 .Flexible

241.5 .Specific construction of distal  
end

241.6 .Having guiding means

237.2 .Surface condition

237.3 .Detection of object or particle  
on surface

237.4 ...On patterned or topographical  
surface (e.g., wafer, mask,  
circuit board)

237.5 .On patterned or topographical  
surface (e.g., wafer, mask,  
circuit board)

237.6 .Having predetermined light  
transmission regions (e.g.,  
holes, aperture, multiple  
material articles)

242.1 **THREAD COUNTING**

243.1 **STANDARD**

243.2 .For fluid suspended particles

243.3 .Flying height testers

243.4 .Surface standard

243.5 .Color

243.6 .Foreign object

243.7 .Texture

243.8 .Light intensity

244 **SAMPLE, SPECIMEN, OR STANDARD  
HOLDER OR SUPPORT (E.G.,  
PLATES OR SLIDES)**

245 .Cotton graders

246 .Fluid containers (e.g., cells or  
cuvettes)

247 **FIDUCIAL INSTRUMENTS**

248 .Artificial reference

249 ..Liquid surface (e.g., bubble  
level)

250 ..Pendular suspension of optical  
element or reticle

251 .Reticle lies outside viewing  
path

252 ..Reticle image transversely  
adjustable relative to optical  
axis

253 .Deflection of line of sight

254 ..Two or more deflections

255 ..By reflection

256 **MISCELLANEOUS**

**CROSS-REFERENCE ART COLLECTIONS**

900 **INTERFEROMETERS (GO1B 9/02)**

901 .Involving fiber optics or  
integrated optics (GO1B 9/02F)

902 .Involving diffraction gratings  
(GO1B 9/02G)

903 .Using holographic techniques  
(GO1B 9/021)

904 **MEASURING MICROSCOPES (GO1B 9/04)**

905 **MEASURING TELESCOPES (GO1B 9/06)**

906 **OPTICAL PROJECTION COMPARATORS,  
E.G., FOR PROFILE (GO1B 9/08)**

907 **GONIOMETERS (GO1B 9/10)**

908 **MEASURING LENGTH, WIDTH, OR  
THICKNESS (GO1B 11/02)**

909 .By means of tv-camera scanning  
(GO1B 11/02B)

910 .By means of diode-array scanning  
(GO1B 11/02C)

911 **MEASURING THE DEFORMATION IN A  
SOLID, E.G., OPTICAL STRAIN  
GAUGE (GO1B 11/16)**

912 **MEASURING ANGLES (GO1C 1/00)**

913 .Theodolites (GO1C 1/02)

914 ..Combined with cameras (GO1C 1/  
04)

915 .Sextants (GO1C 1/08)

916 **ALTIMETERS FOR AIRCRAFT (GO1C 5/  
00A)**

917 **MEASURING INCLINATION, E.G., BY  
CLINOMETERS, BY LEVELS (GO1C  
9/00)**

918 **PHOTOGRAMMETRY; PHOTOGRAPHIC  
SURVEYING (GO1C 11/00)**

919 .Picture taking arrangements  
specially adapted for  
photogrammetry or photographic  
surveying, e.g., controlling  
overlapping of pictures (GO1C  
11/02)

920 ..By scanning the object (GO1C  
11/02A)

921 .Interpretation of pictures (GO1C  
11/04)

922 **PHOTOMETRY, E.G., PHOTOGRAPHIC  
EXPOSURE METER (GO1J 11/04)**

923 **RADIATION PYROMETRY (GO1J 5/00)**

924 **MEASURING VELOCITY OF LIGHT (GO1J  
7/00)**

925 **MEASURING OPTICAL PHASE  
DIFFERENCE: MEASURING OPTICAL  
WAVELENGTH (GO1J 9/00)**

- 926 **MEASURING THE CHARACTERISTICS OF INDIVIDUAL OPTICAL PULSES OR OF OPTICAL PULSE TRAINS (G01J 11/00)**
- 927 **MEASURING VARIATIONS OF OPTICAL PROPERTIES OF MATERIAL WHEN IT IS STRESSED, E.G., BY PHOTOELASTIC STRESS ANALYSIS USING INFRA-RED, VISIBLE LIGHT, ULTRA-VIOLET (G01L 1/24)**
- 928 **INVESTIGATING OR ANALYZING MATERIALS BY THE USE OF OPTICAL MEANS, I.E., USING INFRA-RED, VISIBLE, OR ULTRA-VIOLET LIGHT (G01N 21/00)**
- 929 .Arrangements, or apparatus for facilitating the optical investigation (G01N 21/01)
- 930 ..Cuvette constructions (G01N 21/03)
- 931 .Systems in which incident light is modified in accordance with the properties of material investigated (G01N 21/17)
- 932 ..With opto-acoustic detection, e.g., for gases or analyzing solids (G01N 21/17B)
- 933 ..With calorimetric detection, e.g., with thermal lens detection (G01N 21/17C)
- 934 ..With modulation of one or more physical properties of the sample during optical investigation, e.g., Electra reflectance (G01N 21/17M)
- 935 ..Dichroism (G01N 21/19)
- 936 ..Polarization-affecting properties (G01N 21/21)
- 937 ...Ellipsometry (G01N 21/21B)
- 938 ...Bi-refringence (G01N 21/23)
- 939 ..Color; spectral properties, i.e., comparison of effect of material on the light at two or more different wavelengths or wavelength bands (G01N 21/25)
- 940 ...Colorimeters (G01N 21/25B)
- 941 ....For batch operation, i.e., multi-sample apparatus (G01N 21/25B2)
- 942 ...Arrangements using two alternating lights and one detector (G01N 21/25D)
- 943 ...Using photo-electric detection (G01N 21/27)
- 944 ....For following a reaction, e.g., for determining photometrically a reaction rate (G01N 21/27C)
- 945 ...Investigating relative effect of material at wavelengths characteristic of specific elements or molecules, e.g., atomic absorption spectrometry (G01N 21/31)
- 946 ..Holographic interferometry (G01N 21/45B)
- 947 ..Scattering, i.e., diffuse reflection (G01N 21/47F)
- 948 .Systems in which the material investigated is excited whereby it emits light or causes a change in wavelength of the incident light (G01N 21/62)
- 949 ..Optically excited (G01N 21/63)
- 950 ...Using photolysis and investigating photolyzed fragments (G01N 21/63C)
- 951 ...Florescence; Phosphorescence (G01N 21/64)
- 952 ...Raman scattering (G01N 21/65)
- 953 .Probe photometers (G01N 21/85B)
- 954 .Scan or image signal processing arrangements specially adapted for investigating the presence of flaws or contaminants, e.g., for scan signal adjustments, for detecting different kinds of defects, for compensating for structures (G01N 21/88)
- 955 **MEASURING LINEAR OR ANGULAR SPEED UTILIZING DEVICES CHARACTERIZED BY THE USE OF OPTICAL MEANS, E.G., USING INFRA-RED, VISIBLE, OR ULTRA-VIOLET LIGHT (G01P 3/36)**
- 956 .Using a ring laser (G01P 3/36B)
- 957 .Using diffraction of light (G01P 3/36C)
- 958 .Using photographic means (G01P 3/38)
- FOREIGN ART COLLECTIONS**
- FOR 000 CLASS-RELATED FOREIGN DOCUMENTS**



Any foreign patents or non-patent literature from subclasses that have been reclassified have been transferred directly to FOR Collections listed below. These Collections contain ONLY foreign patents or non-patent literature. The parenthetical references in the Collection titles refer to the abolished subclasses from which these Collections were derived.

FOR 100 **INSPECTION FOR FLAWS OR IMPERFECTIONS (356/237)**  
 FOR 101 .Cloth or thread inspection (356/238)  
 FOR 102 .Passing light through a transparent or translucent article (356/239)  
 FOR 103 ..Containers (e.g., bottles) or contents (356/240)  
 FOR 104 .Bore inspection (e.g., borescopes) (356/241)  
 FOR 105 **THREAD COUNTING (356/242)**  
 FOR 106 **STANDARDS (356/243)**  
 FOR 107 **BY LIGHT INTERFERENCE (E.G., INTERFEROMETERS) (356/345)**  
 FOR 108 .Spectroscopy (356/346)  
 FOR 109 .Holography (356/347)  
 FOR 110 ..For optical configuration (356/348)  
 FOR 111 .With light beams of different frequency (e.g., heterodyning) (356/349)  
 FOR 112 ..For rotation rate (e.g., ring laser) (356/350)  
 FOR 113 .With polarization (356/351)  
 FOR 114 .With partially reflecting plates in series (e.g., Fabry-Perot type) (356/352)  
 FOR 115 .With shearing (356/353)  
 FOR 116 .With wavefront division (e.g., by diffraction) (356/354)  
 FOR 117 ..For dimensional measurement (e.g., thickness) (356/355)  
 FOR 118 ...Of displacement or distance (356/356)  
 FOR 119 .For dimensional measurement (e.g., thickness) (356/357)  
 FOR 120 ..Of displacement or distance (356/358)  
 FOR 121 .For optical configuration (356/359)  
 FOR 122 ..With two light beams (e.g., Twyman-Green) (356/360)

FOR 123 .For refractive indexing (356/361)  
 FOR 124 ..With Schlieren effect (356/362)  
 FOR 125 .For orientation and alignment (356/363)  
 FOR 126 **FOR FLATNESS (356/371)**  
 FOR 127 **BY MENSURATION (356/372)**  
 FOR 128 .Of article displacement (356/373)  
 FOR 129 ..Including moire' fringe (356/374)  
 FOR 130 .Of position (356/375)  
 FOR 131 .Of contour or profile (356/376)  
 FOR 132 ..With curve readers (356/377)  
 FOR 133 .Of cavities (356/378)  
 FOR 134 .Of area or volume (356/379)  
 FOR 135 ..By scanning (356/380)  
 FOR 136 .Of thickness (356/381)  
 FOR 137 ..Of light permeable material (356/382)  
 FOR 138 .Of length (356/383)  
 FOR 139 .Of width or diameter (356/384)  
 FOR 140 ..Of moving object (356/385)  
 FOR 141 ...By scanning or light interruption (356/386)  
 FOR 142 ..By scanning or light interruption (356/387)

